

产品规格书

PRODUCT SPECIFICATION

顾客产品名称型号:

Client Product Name:

HCB产品名称型号:

HCB Product Name:

C39602-BNP (39612双排系列)

产品编号:

Product Number:

HCB7. 865. 1319-1 (HCB-TS-0108)

规格书版本号:

Version Number:

B/3

HCB承认栏 HCB admit bar	批准 Approval	张勤国 2026. 04. 03	审核 Check	连云斌 2026. 04. 03	拟制 Edit	吴宜任 2026. 04. 03
顾客承认栏 Customers admit bar	批准 Approval		审核 Check		确认 Confirm	

地址:中国浙江省乐清市乐清湾港区乐商创业园创新路4号

Tel: 86-577-62351197

Fax: 86-577-62363197

Zip: 325600

DESCRIPTION 变更记录






产品型号名称: Product Name:	C39602-BNP (39612双排系列)
产品编号: Product Number:	HCB7. 865. 1319-1 (HCB-TS-0108)

No. :	REV:	MARK:	DESCRIPTION 变更记录	CHANGED:	DATE:
1	B/1		优化规格书	连云斌	2021.07.17
2	B/2		增加产品名称互配表，更新适用温度	连云斌	2021.11.15
3	B/3	△	更新适配表	吴宜任	2026.04.03

产品规格书
PRODUCT SPECIFICATION

产品名称型号: Product Name:	C39602-BNP (39612双排系列)
产品编号: Product Number:	HCB7. 865. 1319-1 (HCB-TS-0108)
规格书版本号: Version Number:	B/3

一、产品简图 Outline drawing



C39602-B10P (177904-1)	10	15.84	21.86
C39602-B08P (177902-1)	8	11.88	17.9
C39602-B06P (177901-1)	6	7.92	13.94
C39602-B04P (177900-1)	4	/	9.98
产品名称	孔位数	A	B
		尺寸	

适配锁片 Matched retainer	C39602-ANS (1779**-1)	一般公差 General Tolerance	适用范围 Scope	>0~3	>3~18	>18~50	>50~120
适配端子  Matched terminal	C39602-02PT (177915-1)/C39602-01PT (177914-1) C39602-12PT (2232901-1)/C39602-11PT (2232902-1)		公差 Tolerance	±0.15	±0.20	±0.31	±0.55
互配塑件 Matched housing	C39602-BNR (1779**-1) C39602-BNRF (1794**-1)	备注 Mark					 
材料 Material	PA66 高阻燃	本色、蓝色、黄色、红色					

产品规格书
 PRODUCT SPECIFICATION

产品名称型号: Product Name:	C39602-BNP (39612双排系列)
产品编号: Product Number:	HCB7. 865. 1319-1 (HCB-TS-0108)
规格书版本号: Version Number:	B/3

二、适用温度范围 Applicable Temperature Range $-40^{\circ}\text{C}\sim+105^{\circ}\text{C}$

三、绝缘电阻 Insulation Resistance $\geq 1000\text{M}\Omega$

四、耐 压 Withstand Voltage 1500V.AC

五、性能与测试说明 PERFORMANCE AND TESTS DESCRIPTION

产品的设计必须满足以下机械性能及要求

Products will be designed to meet the mechanical and electrical performance requirements specified

	项目 Item	测试条件 Test Condition	规格要求 Requirement	
1	外观 Appearance	目测视力在1.0以上,照明强度为(200~300)lx,目测距离约(0.3~0.5)m. Visual by eye light >1.0,lamp (200~300)lx,space (0.3~0.5)m.	塑料件表面应无明显疤痕、凹陷、开裂及影响使用的变形. Plastic part:Smooth and flat surface without discolor,broken,crack, distortion defects is acceptable.	
2	绝缘电阻 Insulation Resistance	测试电压:500V DC/Min。500V DC 作用于插入端子与护套接触的金属外壳之间。 Test Voltage:500 vcc during 1 minute applied between inserted terminal and a meallic wrapper in contact with the Plastic patr external wall .	$\geq 1000\text{M}\Omega$ MIN	
3	耐电压 Dielectric Strength	用相邻接触件之间或地线之间施加50Hz 1500V AC(有效值),漏电流1mA. Mate connectors,apply 1500V AC for 1 minute between adjacent terminal or ground, leakage current 1mA.	漏电流1mA. leakage current 1mA. 无击穿和飞弧现象 No Breakdown	
4	端子插入力 Contact Insertion Force	端子压紧后,以15-25mm/min的匀速插入塑件中。 Fixing the Plastic part into a support by pulling cable at rate of 25mm/min and in s distance of 15mm from the insulation crimp.The terminal must remain free to pivote during the insertion	P/N	最大力 Max. Effort (Kg/f)
			C39602-BNP (39612双排系列)	1.0
5	端子保持力 Reteintive Force	以25mm/min的速度将插入护套中的端子拔出的力量,塑件在测试之前必须保持在 $23^{\circ}\text{C} \pm 1^{\circ}\text{C}$,48-52%相对湿度的环境中48h,符合IEC规格68-1 Measure the pull out force of the inserted terminal into Plastic part by stretching cable at rate of 25mm/min Plastic part must remain at $23\pm 1^{\circ}\text{C}$,48-52% RH for 48h before test,acc. IEC spec 68-1.	P/N	最小力 Min. Effort (Kg/f)
			C39602-BNP (39612双排系列)	4.0

产品规格书
PRODUCT SPECIFICATION

产品名称型号: Product Name:	C39602-BNP (39612双排系列)
产品编号: Product Number:	HCB7. 865. 1319-1 (HCB-TS-0108)
规格书版本号: Version Number:	B/3

项目 Item	测试条件 Test Condition	规格要求 Requirement
6 耐高温 Heat Resistance	把试件放入高温试验箱中, 以 (0.7~1) °C/min 的温度变化速度, 将温度调到 (105±2) °C. 待平衡后保持4小时, 然后以同样的速度降到室温, 恢复2小时后检查. Heating: Room temperature → (105±2) °C Speed: (0.7~1) °C/min Duration: 4 hours Cooling: (105±2) °C → room temperature at the same speed Check: In 2 hours	外观: 无损伤 Appearance: No Damage
7 耐低温 Cold Resistance	把试件放入低温试验箱中, 以 (0.7~1) °C/min 的温度变化速度, 将温度调到 (-40±2) °C. 待平衡后保持4小时, 然后以同样的速度升到室温, 恢复2小时后检查. Cooling: Room temperature → (-40±2) °C Speed: (0.7~1) °C/min Duration: 4 hours Heating: (-40±2) °C → room temperature at the same speed Check: In 2 hours	外观: 无损伤 Appearance: No Damage
8 阻燃性 Flame Retardancy	灼热丝温度850度, 火热持续时间小于等于30秒; 灼热丝温度750度, 火热持续时间小于等于2秒. Glow-wire temperature 850°C fire heat duration less than 30 seconds. Glow-wire temperature 750°C fire heat duration less than 2 seconds.	符合850度, 符合750度 It fits 850 degrees, meets 750 degrees

六、资格 QUALIFICATION

本规范中描述的产品已全部通过第五点规定的测试, 即按照本规范将被视为合格.

The product described in this specification has to overcome successfully all the tests specified in point 5. Afterwards and according with this specification, it will be considered qualified.